



Re-tuning your digital radio for new stations

***As new digital radio stations switch on, receivers should be re-tuned.
Re-tune your radio regularly so that you don't miss any new Stations!***

***Simply follow the prompts on your receiver menu or
manufacturers have outlined some here on how to do that.***

This summary is a guide and may assist:

Bush BR10DAB – Factory Reset

Hold down the Menu button, and if will prompt: “Press INFO to confirm reset”. Press the INFO button, and the radio will reset and rescan for DAB+ stations

Grundig Models – Factory Reset

Press the Radio Menu Button on the unit, select “Main Menu” using the arrows and then select “Factory Reset”. Press the INFO button and the radio will reset and rescan for DAB+ stations. Once the radio has reset, the user will then need to select “Full Scan” from the Main Menu.

Revo Models – Factory Reset

Press the Menu Button on the unit, select “Main Menu” using the arrows and then select System Setup, then select “Factory Reset”. Press the INFO button and the radio will reset and rescan for DAB+ stations

Sangean WFT-1D – Factory Reset

To get into the DAB menu option, press the TUNING knob when listening to a station. Press the MENU button. Scroll down and select “System Settings” using the TUNING knob. Scroll down and select “Factory Reset”. Confirm that you wish to initiate a “Factory Reset”. The unit will switch on after the factory reset. Press the STANDBY button to power on the unit. From the menu select “DAB”. The receiver will initiate a “LOCAL SCAN”, please wait for this to complete. On the DAB menu select FULL SCAN to tune the receiver to services.

Pure Classic One – Factory Reset

When the unit is switch on and in DAB mode. Hold down the MENU button until a version number is displayed on the display. Using the knob, scroll through the options till “Factory Reset” is shown. Press on the knob to select this option. Press on the knob again to initiate a “Factory Reset”. The unit will initiate a power cycle after it has completed “Factory Reset” and a FULL AUTOTUNE to tune the receiver to services.



Pure Evoke Flow – Trim Stations

When listening to a DAB station tap O Options and highlight and select 'DAB settings'. Highlight and select 'Trim station list' to remove inactive DAB stations (marked '?') from the station list.

Pure Evoke Flow – Factory Reset

Resetting your radio removes all DAB and FM presets (but not your internet Favourites), clears the DAB station list and resets all options to defaults. All your wireless networks settings will be cleared.

1. Press and hold O Options for 3 seconds to display the 'Factory reset' menu.
2. Tap O Yes to confirm the reset or O No to cancel, or wait 7 seconds for the screen to time-out.

Roberts WM-202

Press the MENU button. Scroll down and select "System Settings" using the TUNING knob. Scroll down and select "Factory Reset". Confirm that you wish to initiate a "Factory Reset". The unit will switch off after the factory reset. Press the On/Off button to power on the unit. From the menu select "DAB". The receiver will initiate a "LOCAL SCAN", please wait for this to complete. On the DAB menu select FULL SCAN to tune the receiver to services.